




IGBT Modules

V_{CES}	650V
I_c	150A

Applications

- Inverter for motor drive
- AC and DC servo drive amplifier
- UPS (Uninterruptible Power Supplies)
- Soft switching welding machine



Features

- Low $V_{ce(sat)}$ with Trench technology
- $V_{ce(sat)}$ with positive temperature coefficient
- High short circuit capability(10us)
- Including ultra fast & soft recovery anti-parallel FWD
- Low inductance
- Maximum junction temperature 175°C

● IGBT

Absolute Maximum Ratings

Parameter	Symbol	Conditions	Value	Unit
Collector-Emitter Voltage	V_{CES}	$V_{GE}=0V, I_c=4mA, T_{vj}=25^{\circ}C$	650	V
Continuous Collector Current	I_c	$T_c=100^{\circ}C$	150	A
Repetitive Peak Collector Current	I_{CRM}	$t_p=1ms$	300	A
Gate-Emitter Voltage	V_{GES}	$T_{vj}=25^{\circ}C$	± 20	V
Total Power Dissipation	P_{tot}	$T_c=25^{\circ}C$ $T_{vjmax}=175^{\circ}C$	468	W



Characteristic values

Parameter	Symbol	Conditions	Value			Unit	
			Min.	Typ.	Max.		
Gate-emitter Threshold Voltage	$V_{GE(th)}$	$V_{GE}=V_{CE}, I_C=2.4mA, T_{vj}=25^{\circ}C$	5.0	5.8	6.5	V	
Collector-Emitter Cut-off Current	I_{CES}	$V_{CE}=650V, V_{GE}=0V, T_{vj}=25^{\circ}C$			1.0	mA	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=150A, V_{GE}=15V, T_{vj}=25^{\circ}C$		1.55	1.80	V	
		$I_C=150A, V_{GE}=15V, T_{vj}=125^{\circ}C$		1.70			
		$I_C=150A, V_{GE}=15V, T_{vj}=150^{\circ}C$		1.75			
Input Capacitance	C_{ies}	$V_{CE}=25V, V_{GE}=0V,$ $f=1MHz, T_{vj}=25^{\circ}C$		9.7		nF	
Reverse Transfer Capacitance	C_{res}			0.45		nF	
Internal Gate Resistance	R_{gint}			2.0		Ω	
Gate-Emitter leakage current	I_{GES}	$V_{CE}=0V, V_{GE}=20V, T_{vj}=25^{\circ}C$			400	nA	
Turn-on Delay Time	$t_{d(on)}$	$I_C=150A$ $V_{CE}=300V$ $V_{GE}=\pm 15V$ $R_G=3.3\Omega$ $T_{vj}=25^{\circ}C$		184		ns	
Rise Time	t_r			49		ns	
Turn-off Delay Time	$t_{d(off)}$			312		ns	
Fall Time	t_f			90		ns	
Energy Dissipation During Turn-on Time	E_{on}			1.05		mJ	
Energy Dissipation During Turn-off Time	E_{off}			3.72		mJ	
Turn-on Delay Time	$t_{d(on)}$		$I_C=150A$ $V_{CE}=300V$ $V_{GE}=\pm 15V$ $R_G=3.3\Omega$ $T_{vj}=125^{\circ}C$		200		ns
Rise Time	t_r				65		ns
Turn-off Delay Time	$t_{d(off)}$				384		ns
Fall Time	t_f				120		ns
Energy Dissipation During Turn-on Time	E_{on}			1.57		mJ	
Energy Dissipation During Turn-off Time	E_{off}			5.17		mJ	
Turn-on Delay Time	$t_{d(on)}$	$I_C=150A$ $V_{CE}=300V$ $V_{GE}=\pm 15V$ $R_G=3.3\Omega$ $T_{vj}=150^{\circ}C$			207		ns
Rise Time	t_r				73		ns
Turn-off Delay Time	$t_{d(off)}$				405		ns
Fall Time	t_f				138		ns
Energy Dissipation During Turn-on Time	E_{on}			1.88		mJ	
Energy Dissipation During Turn-off Time	E_{off}			5.68		mJ	
SC Data	I_{sc}		$t_p \leq 6\mu s, V_{GE}=15V,$ $T_{vj}=150^{\circ}C, V_{cc}=300V,$ $V_{CEM} \leq 650V$		750		A



● Diode

Absolute Maximum Ratings

Parameter	Symbol	Conditions	Value	Unit
Repetitive Peak Reverse Voltage	V_{RRM}	$T_{vj}=25^{\circ}C$	650	V
Continuous DC Forward Current	I_F		150	A
Repetitive Peak Forward Current	I_{FRM}	$t_p=1ms$	300	A
I^2t -value	I^2t	$V_R=0V, t_p=10ms, T_{vj}=125^{\circ}C$	2050	A ² s
		$V_R=0V, t_p=10ms, T_{vj}=150^{\circ}C$	1950	

Characteristic values

Parameter	Symbol	Conditions	Value			Unit
			Min.	Typ.	Max.	
Forward Voltage	V_F	$I_F=150A, T_{vj}=25^{\circ}C$		1.55		V
		$I_F=150A, T_{vj}=125^{\circ}C$		1.45		
		$I_F=150A, T_{vj}=150^{\circ}C$		1.40		
Recovered Charge	Q_{rr}	$I_F=150A$		2.44		μC
Peak Reverse Recovery Current	I_{rr}	$V_R=300V$ $-di_F/dt=2200A/\mu s$		70		A
Reverse Recovery Energy	E_{rec}	$T_{vj}=25^{\circ}C$		0.85		mJ
Recovered Charge	Q_{rr}	$I_F=150A$		3.24		μC
Peak Reverse Recovery Current	I_{rr}	$V_R=300V$ $-di_F/dt=2200A/\mu s$		102		A
Reverse Recovery Energy	E_{rec}	$T_{vj}=125^{\circ}C$		1.32		mJ
Recovered Charge	Q_{rr}	$I_F=150A$		3.61		μC
Peak Reverse Recovery Current	I_{rr}	$V_R=300V$ $-di_F/dt=2200A/\mu s$		123		A
Reverse Recovery Energy	E_{rec}	$T_{vj}=150^{\circ}C$		1.51		mJ



● Module Characteristics





$T_c=25^{\circ}\text{C}$ unless otherwise specified





Parameter	Symbol	Conditions	Value			Unit
			Min.	Typ.	Max.	
Isolation voltage	V_{isol}	$t=1\text{min}, f=50\text{Hz}$	2500			V
Maximum Junction Temperature	T_{jmax}				175	$^{\circ}\text{C}$
Operating Junction Temperature	$T_{\text{vj op}}$		-40		150	$^{\circ}\text{C}$
Storage Temperature	T_{stg}		-40		125	$^{\circ}\text{C}$
Thermal Resistance Junction-to Case	$R_{\theta\text{JC}}$	per IGBT			0.32	K/W
		per Diode			0.50	
Thermal Resistance Case-to Sink	$R_{\theta\text{CS}}$	Conductive grease applied		0.15		K/W
Comparative Tracking Index	CTI			>200		
Module Electrodes Torque	M_t	Recommended(M5)	3.0		5.0	N·m
Module-to-Sink Torque	M_s	Recommended(M6)	3.0		5.0	N·m
Weight of Module	G			150		g





MG150HF065TLC1

RoHS
COMPLIANT











Circuit Diagram



● Package Outline Information

Dimensions in Millimeters





Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.